

# PMU Placement to Ensure Observable Frequency and Voltage Dynamics:

A Structured System Approach

**Qixing Liu** 

(Joint work with Sergio Pequito, Prof. Soummya Kar and Prof. Marija Ilic)

Electrical and Computer Engineering
Carnegie Mellon University
Instituto Superior Técnico

8th ANNUAL CMU CONFERENCE ON THE ELECTRICITY INDUSTRY

**DATA-DRIVEN SUSTAINABLE ENERGY SYSTEMS** 

INSTITUTO SUPERIOR TÉCNICO



### **Outline**


- **♦** Static Observability vs Dynamic Observability
- **♦** The key role of Phasor Measurement Units
- Coupled Frequency-Voltage Dynamic Model
- Structural Systems
- PMU Placement



### Static Observability vs Dynamic Observability

### **Topological Static Observability** [Abur 1995]

### **Covering problem (IEEE 14 Example)**






### Static Observability vs Dynamic Observability

### **Mutual Information to Improve Static Observability** [Li 2011]

Mutual information (MI): the amount of information that PMU measurement carries about the system state

### **Placement Objective:** Maximize mutual information



**IEEE 14-Bus: 3 PMUs** 





### Static Observability vs Dynamic Observability

### **Dynamic Observability**

A system is said to be observable if, for any possible sequence of state and control vectors, the current state can be determined in finite time using only the outputs.

(Descriptor form)
$$E\dot{x} = Ax$$

$$y = Cx$$
DAEs vs ODEs
$$\dot{x} = Ax$$

$$y = Cx$$

$$y = Cx$$




### The Key Role of Phasor Measurement Units

**◆** Real-time synchronized measurements for geographically large-scale systems

**◆** Enable systematically designed dynamic observer



### Modeling Power Systems **Coupled frequency-voltage dynamics**



#### Load

-Induction Machine

#### **Network coupling constraints**

-Linear Algebraic Equations (KCL, KVL and Ohm's Law)

### **States of generator**

-Electromechanics:  $[\Delta \delta_G, \Delta \omega G]$ 

-Electromagnetics: [E'D, E'Q]

-Speed-governor:  $[\Delta P_T, \Delta a]$ 

-Excitation control: [V<sub>R</sub> , efd, V<sub>F</sub>]

### **Standard state-space model**

$$\underline{\dot{x}} = A\underline{x} + B\underline{u}_G + F\underline{w}$$



### Problem Statement




Given only the dynamics/structure

$$\dot{x} = Ax$$

How to design

$$y = Cx$$

Such that (A,C) is observable, I.e,



### PMU Placement






### Structural Systems

### Representation of the dynamics as digraph


### From

$$\begin{pmatrix} \dot{x}_1(t) \\ \dot{x}_2(t) \\ \dot{x}_3(t) \end{pmatrix} = \begin{pmatrix} 0 & 0 & 0 \\ a_{21} & 0 & a_{23} \\ a_{31} & a_{32} & 0 \end{pmatrix} \begin{pmatrix} x_1(t) \\ x_2(t) \\ x_3(t) \end{pmatrix}$$







### Given the system Digraph




### Does it have a substructure as follows

















# PMU = # Cacti






### Case Study: 5 bus





### Is this system dynamically observable?






**Number of states: 37** 






## Electrical & Computer ENGINEERING Information and Communication Technologies Institute Carnegie Mellon | PORTUGAL

### Compute one tree [Node 1-Tree (Path 1-37)]












### Compute one tree [Node 4-Tree (Path 4-22)]



| Measured States | 4, 30, 34  |
|-----------------|--|
| Interpretation  | Hydro G1 Angle (4)<br>Load 1 Angle (30)<br>Load 2 Angle (34) |
| Buses           | 1, 4, 5  |
| # PMUs          | 3  |



### Final combinations with minimum number of sensors

| Measured States | 4, 30, 34  |
|-----------------|--|
| Interpretation  | Hydro G1 Angle (4)<br>Load 1 Angle (30)<br>Load 2 Angle (34) |
| Buses           | 1, 4, 5  |
| # PMUs          | 3  |



### Conclusions and Further Research

- ◆ Implement this framework in IEEE 14/20/30 bus
- Robustness analysis and quantitative analysis
- User friendly toolbox



### References

- [1] Ali Abur, Optimal Plancement of Phasor Measurement Units for State Estimation. PSERC Report, 2005
- [2] Qiao Li, Tao Cui, Yang Weng, Rohit Negi, Franz Franchetti, Marija Ilic, An Information-Theoretic Approach to PMU Placement in Electric Power Systems
- [3] PMU Placement to Ensure Observable Frequency and Voltage Dynamics: A Structured System Approach, 8<sup>th</sup> CMU Electricity Conference. http://www.ece.cmu.edu/~electriconf/index.html
- [4] Sergio Pequito, S. Kar, A. Pedro Aguiar, Actuator Placement Design Strategies for Controllability of Large Scale Systems: Minimality through Structured Systems, *To be submitted to Transactions of Automatic Control*





### Questions?

Sergio Pequito: spequito@andrew.cmu.edu

Qixing Liu: <a href="mailto:lqx@cmu.edu">lqx@cmu.edu</a>

Prof. Soummya Kar: soummyak@andrew.cmu.edu

Prof. Marija Ilic: milic@ece.cmu.edu

